

Pressure washing marked vehicles?




Always remember

15-1-80-Wide

SPRAY ANGLE
15° Max (Vertical/Horizontal)




NOZZLE DISTANCE
1 Metre Minimum



NOZZLE PRESSURE
80 bar (1000 psi) Max



WIDE FAN PATTERN



Other useful washing tips for vehicles marked with 3M™ Diamond Grade™ Conspicuity Markings

Dirty Edges: Any dirt collecting at the outer edges of vehicle markings will not affect the overall product performance. **Do not attempt to remove this dirt with aggressive use of pressure washing equipment** as it may result in edge lifting and/or top film layer delamination.

Water Temperature: 60°C maximum.

Cleaning Solutions: Do **not** use acid or solvent cleaning solutions.

Alternative washing methods

Sponge/Soft Cloth: Use cold or warm water and soap/detergent, followed by a clean water rinse.

Automatic Washers: 3M™ Diamond Grade™ conspicuity markings will withstand repeated cleaning by automatic rotary brush washers.

3M Innovation

For further advice contact 3M Technical Group on 01344 866263. For more copies of this poster contact freephone: 0800 1695268 quoting Poster Ref EA797

3M Commercial Graphics Group 3M United Kingdom PLC, 3M House, 28 Great Jackson Street, Manchester M15 4PA. 3M Commercial Graphics Group 3M Ireland 3M House, Adelphi Centre, Upper Georges Street, Dun Laoghaire, Co. Dublin, Ireland